



8.1LT

	Rev: A		8.1L CAC			
	Units		1500		1800	
	Std	Metric				
General Engine Data						
Type	N/A		In-Line 4 cycle			
Number of cylinders	N/A		6			
Aspiration	N/A		Turbo Charge Air Cooled			
Bore	in	mm	4.37	111	4.37	111
Stroke	in	mm	5.47	139	5.47	139
Displacement	in^3	L	492	8.1	492	8.1
Compression Ratio	N/A		10.5			
Mean Piston Speed	ft/min	m/s	1368	6.95	1641	8.34
Gross Standby Power Rating^{1,2,3} Per ISO 3046 at the Flywheel						
NG	Hp	kW	194	145	239	178
LP	Hp	kW	137	102	164	122
MEP (@ rated Load on NG)	psi	bar	209	14	213	15
MEP (@ rated Load on LP)	psi	bar	147	10	146	10
Gross Prime Power Rating^{1,2,3} Per ISO 3046 at the Flywheel						
NG	Hp	kW	175	131	200	149
LP	Hp	kW	N/A	N/A	N/A	N/A
MEP (@ rated Load on NG)	psi	bar	188	13	179	12
MEP (@ rated Load on LP)	psi	bar	N/A	N/A	N/A	N/A
RPM Range (Min-Max)	RPM		1500-2000			
Rotation Viewed from Flywheel	N/A		Counter Clockwise			
Firing Order	N/A		1-5-3-6-2-4			
Dry Weight						
Fan to Flywheel	lb	kg	2200	998	2200	998
Rad to Flywheel	lb	kg	2660	1207	2660	1207
Wet Weight						
Fan to Flywheel	lb	kg	2288	1042	2288	1022
Rad to Flywheel	lb	kg	2860	1311	2860	1292
CG						
Distance from FW housing	in	mm	17	426	17	426
Distance above center of crankshaft	in	mm	7	184	7	184
Engine Mounting						
Maximum Allowable Bending Moment at Rear of Block	lb ft	N m				
Moment of Inertia About Roll Axis	lb ft^2	kg m^2				
Flywheel housing	N/A		SAE No 2			
Flywheel	N/A		No 11 1/2			
Number of Flywheel Teeth	N/A		140			
Exhaust System						
Type			Water Cooled Manifold			
Maximum allowable Back pressure	in HG	kPa	3	10.2	3	10.2
Standard Catalyst Back pressure	in HG	kPa	1.5	5.1	1.5	5.1
Exhaust Outlet Pipe Size						
Maximum Turbine Inlet Temperature	F	C	1382	750	1382	750
Exhaust Flow at Rated Power	lb/hr	kg/hr	1241	563	1481	672
Exhaust Flow at Rated Power @1350F	cfm	m^3/min	946	26.8	1129	31.9
Air Induction System						
Maximum allowable Intake Air Restriction with Air Cleaner						
Clean	inH2O	kPa	5	1.24	5	1.24
Dirty	inH2O	kPa	15	3.74	15	3.74
Combustion Air required	lb/hr	kg/hr	1171	531	1397	634
Combustion Air required	cfm	m^3/min	297	8	355	10



8.1LT

	Rev: A		8.1L CAC			
	Units		1500		1800	
	Std	Metric				
Electrical System						
Minimum Recommended Battery Capacity	AH		150			
Cold Cranking Current						
Engine only	CCA		900			
Engine with Drive train	CCA		900			
Maximum Allowable Resistance of Starting Circuit	Ohms		0.002			
Starting Motor Power	HP	kW	6.0	4.5	6.0	4.5
Battery Charging Alternator						
Voltage	Volts		24			
Current	Amps		45			
Coil primary Resistance	Ohms		0.590 ± 10%			
Spark Plug p/n			IFR7F-4D			
Spark plug gap	inches	mm	.015" (-0/+ .008")		.38mm (-0/+ .2mm)	
Cooling System						
Coolant Capacity						
Engine only	gal	L	5	22.7	5	22.7
Engine with Radiator	gal	L	17.5	80	17.5	80
Engine Coolant Flow	gal/min	L/min	53	200	63	240
Water Pump Speed	RPM		1950		2340	
Heat rejected to Cooling water at rated Load	btu/min	kcal/sec	7690	32.3	9357	39.3
Maximum Intake Air Temperature (IAT)	F	C	155	68	155	68
ECU IAT Warning	F	C	140	60	140	60
ECU IAT Shutdown	F	C	155	69	155	69
Maximum Coolant Friction Head External to the engine	psi	bar	5.8	0.4	5.8	0.4
Maximum Air Restriction Across a Radiator	inH2O	mmH2O	0.5	12.8	0.5	12.8
Standard Thermostat Range						
Cracking Temperature	F	C	160	71	160	71
Full Open Temperature	F	C	185	85	185	85
Maximum Allowable Pressure Cap	psi	bar	14.7	1	14.7	1
Ambient Clearance Open Genset (water) (Air-to-Boil)						
Specified	F	C	142	61	142	61
Acutal	F	C			149	65
Ambient Clearance (Oil)						
Specified	F	C	142	61	142	61
Acutal	F	C			145	63
CAC Rise over Ambient (Charge)						
Specified	F	C	15	9	15	9
Acutal	F	C			14	8
Maximum Allowable Top Tank Temperature	F	C	230	110	230	110
ECU Warning	F	C	220	104	220	104
ECU Shutdown	F	C	230	110	230	110
Fan Power	HP	kW	4.5	3.4	8.0	7.5
Fan Diameter, including blades	in	mm	28	711	28	711
Fan Speed	RPM		1950		2340	
Cooling Fan Air Flow @ 1" Static H2O Pressure and 125F @ radiator	CFM	m ³ /min	10,714	303	12,500	354
Charge Air Cooler						
Compressor Outlet Temperature	F	C	225	107	230	110
Compressor Flow Rate	lb/hr	kg/hr	1241	563	1481	672
Heat Rejection per CAC	btu/min	kW	TBD		760	13.4



8.1LT

Rev:	A
Units	
Std	Metric
8.1L CAC	
1500	1800

Lubrication System							
Oil Specification				SAE 15W-40 Low Ash Gas engine oil (.25-.5% by wt), API CD/CF or higher			
Oil Pressure							
Idle							
Min	Psi	Bar	11	0.8	11	0.8	
Max	Psi	Bar	20.3	1.4	20.3	1.4	
Rated Speed							
Min	Psi	Bar	20.3	1.4	20.3	1.4	
Max	Psi	Bar	70	4.8	70	4.8	
Maximum Allowable Oil Temperature	F	C	250	121	250	121	
Engine Oil Capacity							
Min	Qts	L	18	17	18	17	
Max	Qts	L	25	24	25	24	
Oil Filter Capacity	Qts	L	3.75	3.5	3.75	3.5	
ECU Oil Pressure Warning ⁵	psi		30				
ECU Oil Pressure Shut Down ⁵	psi		25				

Fuel System							
Fuel Consumption ⁶							
NG	Ft ³ /hr	kg/hr	1269	29	1539	35	
LP	Ft ³ /hr	kg/hr	420	22	517	28	
Maximum EPR Rated Pressure	psi	kPa	1.0	6.9	1.0	6.9	
Maximum Running pressure to Electronic Pressure Regulator (EPR)	inH2O	kPa	11.0	2.7	11.0	2.7	
Minimum Running pressure to EPR	inH2O	kPa	7.0	1.7	7.0	1.7	
Minimum Gas Supply Pipe Size			1-1/4" NPT				
Maximum EPR Rated Pressure	psi	kPa	1.0	6.9	1.0	6.9	
Maximum Running Pressure to EPR	inH2O	kPa	11.0	2.7	11.0	2.7	
Minimum Running Pressure to EPR	inH2O	kPa	7.0	1.7	7.0	1.7	
Minimum LPG Supply Pipe Size ⁴			1-1/4" NPT				

The preceding pipe sizes are only suggestions and piping sizes may vary with temperature, pressure, distance from supply and application of local codes. Gas must be available at adequate volume and pressure for engine at the EPR.

¹ Standby and overload ratings based on ISO3046.
² All ratings are gross flywheel horsepower corrected to 77°F at an altitude of 328feet with no cooling fan or alternator losses using heating value for NG of 1015 BTU/SCF.
³ Production tolerances in engines and installed components can account for power variations of +/- 5%. Altitude, temperature and excessive exhaust and intake restrictions should be applied to power calculations.
⁴ The preceding pipe sizes are only suggestions and piping sizes may vary with temperature, pressure, distance from supply and application of local codes. Gas must be available at adequate volume and pressure for engine at the EPR.
⁵ >1400RPM
⁶ See NGE Technical Spec. 56300002 - Fuel Specification